

Solar-Log™ Installation Housing for Outdoor Use

Protection Against Dust and Moisture

The Solar-Log™ provides reliable protection to ensure safe operation under all weather conditions with protection against dust and moisture. The housing is available in two versions. The housing can be equipped with a Solar-Log™ and other components, e.g. an external communication module. In addition to the Solar-Log™ socket, a second socket is included.



Technical data	Version 1	Version 2
Installation Housing	The housing material is made of polycarbonate and ABS plastic.	
	For quick and easy installation of the Solar-Log™, the holes on the mounting wall have been pre-drilled.	
Mounting	There is space in the box for additional components.	
	4 PG connections are available for the grid power network and other connections.	5 PG connections are available for the grid power network and other connections.
	To mount the data logger properly, please remove the mounting plate from the installation and then mount the Solar-Log™ device. Then screw the mounting plate back on.	
Standard color for the enclosure	Gray / RAL 7035	
Surface	The Installation Housing is non-fading.	
Power sockets	2 pieces, power cable provided by the customer	3 pieces, 1 m power cable with angle plug
Protection class	IP 65 when used with the proper cable screws and when the cable conduits are properly sealed.	
Dimensions (w x h x d) in mm, Weight in kg	400 x 300 x 130, 3.53	600 x 300 x 130, 5.25
Warranty	2 years	2 years
Article number	255422	220063